QO124L125PGC

Load center, QO, 1 phase, 24 spaces, 34 circuits, 125A convertible main lugs, PoN, NEMA1, gnd bar, combo cover, UL





Main

Mani	
Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Combination flush/surface cover

Complementary

Main lugs 50 lb.in, AWG 6AWG 2/0, aluminium/copper
Main lugs
125 A
24
65 kA
34
10
1 phase
AWG 6AWG 2/0 aluminium/copper
Grounding bar included (not installed)
Lugs
3-wire
Tin plated copper busbar
Welded sheet steel
Baked enamel Gray
7
20.91 in (531 mm)
14.25 in (362 mm)

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	10003-QO PON 1PH LC,12-60 CKT, ML N1
Discount Schedule	DE3A
GTIN	785901978374
Nbr. of units in pkg.	1
Package weight(Lbs)	20.28 lb(US) (9.199 kg)

Returnability	Yes
Country of origin	US

Packing Units

PCE
5.80 in (14.732 cm)
16.10 in (40.894 cm)
23.60 in (59.944 cm)
PAL
35
750.00 lb(US) (340.194 kg)
45.60 in (115.824 cm)
40.00 in (101.6 cm)
48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile