



CUT LEVEL 3 NITRILE DIPPED GLOVES

ULTIMATE DURABILITY. ALL DAY COMFORT.



| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|---|----|
| Abrasion | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tearing | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (TDM Test) | A | B | C | D | E | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTWIPE™ Touch
Screen Compatible
Fingertips & Palms

High Dexterity
Fingertips

Web Grip
More comfortable fit

Breathable Back

Best-in-Class
Puncture Resistance

Color-Coded Bands
Easy cut level
identification



SPECIFICATIONS

| | |
|----------------|---------------------------|
| Gauge | 15 |
| Liner Material | Nylon and HPPE Blend Knit |
| Dip Material | Nitrile |
| Cuff Style | Elasticated Knit |

RECOMMENDED APPLICATIONS

- Demolition
- Material Handling
- Oily & Wet Conditions
- General Work
- Wire Stripping
- Pipe Threading
- Cutting

CARE INSTRUCTIONS

Machine wash warm water (105°F),
mild detergent, no bleach.
Line dry.

| SIZE | 1 PAIR | 12 PAIR (Contractor Pack) |
|------|------------|---------------------------|
| S | 48-22-8930 | 48-22-8930B |
| M | 48-22-8931 | 48-22-8931B |
| L | 48-22-8932 | 48-22-8932B |
| XL | 48-22-8933 | 48-22-8933B |
| XXL | 48-22-8934 | 48-22-8934B |

SEE MORE PPE



or visit <https://qr.mke.it/2hz48>



Milwaukee

CUT LEVEL 3

9" / L
48-22-9932

SHOCKSOFT™

